

WHAT IS CLAIMED

1. A method of controlling the operation of a plurality of transceiver stations from a master site comprising the steps of:

5 (a) transmitting, from said master site to said transceiver stations, a general application information signal that is retransmitted by each of said transceiver stations;

(b) storing, in a respective transceiver station, a  
10 sequence of commands which, when invoked, cause said respective transceiver station to perform a respective sequence of actions, including the transmission of one or more additional specific application information signals, other than said general application information signal as  
15 received from said master site and retransmitted by said respective transceiver station, and wherein the respective sequence of actions of one transceiver station is not necessarily the same as, and can be expected to be different from the respective sequence of actions of  
20 another transceiver station of said plurality of transceiver stations;

(c) transmitting, from said master site to each of said transceiver stations, a prescribed command signal; and

25 (d) at said each of said transceiver stations, receiving said prescribed command signal transmitted from said master site in step (c) and, in response thereto,

invoking the respective sequence of commands stored in  
step (b), and thereby causing each respective transceiver  
30 station to perform a respective sequence of actions  
associated with the respective sequence of commands stored  
thereby.

2. The method according to claim 1, wherein step  
(b) comprises transmitting respectively different  
sequences of commands from said master site to  
5 respectively different ones of said transceiver stations,  
and conditionally storing said respectively different  
sequences of commands at said respectively different ones  
of said transceiver stations under the same command name,  
and wherein step (d) comprises, in response to receipt of  
10 said prescribed command signal at said respectively  
different ones of said transceiver stations, invoking  
respective sequences of commands stored in step (b), and  
thereby causing said respectively different ones of said  
transceiver stations to perform respectively different  
15 sequences of actions associated with the invoked same  
sequences of commands.

3. The method according to claim 2, wherein step  
(a) comprises broadcasting, from said master site to said  
transceiver stations, common commercial audio programming  
5 that is rebroadcast by each of said plurality of  
transceiver stations as it is received.

4. The method according to claim 3, wherein a  
respective sequence of commands stored at a respective  
transceiver station includes commands that are effective  
5 to play back respectively different information files  
stored at said respective transceiver station interleaved  
with portions of said common commercial audio programming  
being rebroadcast by said respective transceiver station.

5. The method according to claim 3, wherein a  
respective sequence of commands stored at a respective  
transceiver station includes commands that are effective  
to cause said respective transceiver station to perform a  
5 sequence of respectively different operations at given  
instances in time.

6. The method according to claim 1, wherein a  
respective sequence of commands comprises a script file  
whose contents are defined so as to control the operation  
5 of a respective transceiver station, including rebroadcast  
thereby of said common commercial audio programming, as  
well as additional functions, including play back of  
respectively different information files stored at said  
respective transceiver station, interleaved with portions  
10 of said common commercial audio programming being  
rebroadcast by said respective transceiver station.

7. The method according to claim 1, wherein step  
(d) further includes, at a respective transceiver station,  
processing one or more additional sequences of commands  
from one or more sources other than said master site, and  
5 causing said respective transceiver station to perform one  
or more additional conditional sequences of actions  
associated with said one or more additional sequences of  
commands.

8. The method according to claim 7, wherein step  
(d) includes sequentially polling or waiting for multiple  
sequences of commands coupled thereto, and causing said  
respective transceiver station to perform action defined  
5 by the oldest yet to be executed current command of a  
respectively polled or received sequence of commands, and  
then transition to another sequence of commands and  
perform action defined by the oldest yet to be executed  
command of said another sequence of commands, prior to  
10 causing said respective transceiver station to perform  
action defined by the next to the oldest yet to be  
executed command of said respectively polled sequence of  
commands.

9. A store and forward communication system  
comprising:

a master site transmitter which is operative to  
transmit a general application information signal to a

5 plurality of transceiver stations, said plurality of  
transceiver stations being operative to receive and  
retransmit said general application information signal,  
and wherein said master site is further operative to  
controllably transmit a prescribed command signal to each  
10 of said transceiver stations;

a respective transceiver station containing a storage  
unit storing a sequence of commands which, when executed,  
cause said respective transceiver station to perform a  
respective sequence of actions, including the transmission  
15 of one or more additional specific application information  
signals, other than said general application information  
signal as received from said master site transmitter and  
retransmitted by said respective transceiver station, and  
wherein a respective sequence of actions of one  
20 transceiver station is not necessarily the same as, and  
can be expected to be different than, the respective  
sequence of actions of another transceiver station of said  
plurality of transceiver stations; and wherein

each of said transceiver stations includes a command  
25 signal processor, which is operative to access and execute  
a sequence of commands stored in said storage unit, in  
response to receipt of said prescribed command signal, and  
thereby cause said each respective transceiver station to  
perform a respective potentially locally unique sequence  
30 of actions associated with the accessed sequence of  
commands.

10. The store and forward communication system according to claim 9, wherein said master site transmitter is operative to transmit respectively different sequences of commands to respectively different ones of said 5 transceiver stations, and wherein storage units thereof are operative to store said respectively different sequences of commands, and wherein command signal processors of respectively different transceiver stations are operative to access and execute respective sequences 10 of commands stored in associated storage units, and thereby cause said respectively different ones of said transceiver stations to perform respectively different sequences of actions associated with the executed sequences of commands.

11. The store and forward communication system according to claim 10, wherein said master site transmitter is operative to broadcast to said transceiver 5 stations, common commercial audio programming that is rebroadcast by each of said plurality of transceiver stations as it is received.

12. The store and forward communication system according to claim 11, wherein a respective sequence of commands stored at a respective transceiver station includes commands that are effective to play back

5    respectively different information files stored in the  
storage unit of said respective transceiver station,  
interleaved with or overlaid on portions of said common  
commercial audio programming being rebroadcast by said  
respective transceiver station.

13.    The store and forward communication system  
according to claim 11, wherein a respective sequence of  
commands stored in a storage unit at a respective  
transceiver station includes commands that are effective  
to cause said respective transceiver station to perform a  
sequence of operations at different instances in time.

14.    The store and forward communication system  
according to claim 9, wherein a respective sequence of  
commands comprises a script file whose contents are  
defined so as to control the operation of a respective  
5    transceiver station, including rebroadcast thereby of said  
common commercial audio programming, as well as additional  
functions, including play back of respectively different  
information files stored at said respective transceiver  
station, interleaved with or overlaid on portions of said  
10    common commercial audio programming being rebroadcast by  
said respective transceiver station.

15.    The store and forward communication system  
according to claim 9, wherein the command signal processor

of a respective transceiver station is operative to process one or more additional sequences of commands from one or more sources other than said master site, and to cause said respective transceiver station to perform one or more additional sequences of actions associated with said one or more additional sequences of commands.

16. The store and forward communication system according to claim 15, wherein the command signal processor of a respective transceiver is operative to poll or await reception of multiple sequences of commands coupled thereto, and to cause said respective transceiver station to perform action defined by the oldest yet to be executed current command of a respectively polled or received sequence of commands, and then transition to another sequence of commands and perform action defined by the oldest yet to be executed command of said another sequence of commands, prior to causing said respective transceiver station to perform action defined by the next to the oldest yet to be executed command of said respectively polled sequence of commands.

17. A store and forward receiver for use with a respective rebroadcasting station of a multistation network having a master site transmitter which transmits a general application information signal to a plurality of rebroadcasting stations, said respective rebroadcasting



station being operative to receive and retransmit said general application information signal, said store and forward receiver comprising:

10 a demodulator which is operative to demodulate a signal transmitted to said plurality of rebroadcast stations from said master site transmitter containing said general application information signal and a control channel;

15 a rebroadcast signal transport path coupled to said demodulator and being operative to coupled said general application information signal to rebroadcasting equipment of said respective rebroadcasting station for rebroadcast thereby; and

20 a command signal processor coupled to said demodulator and said rebroadcast signal transport path, and which is operative, in response to receipt of a prescribed command in said control channel of said signal transmitted from said master site transmitter to said plurality of rebroadcasting stations, to access a sequence  
25 of commands stored in a storage unit therefor, and to cause the execution of respective actions associated with said sequence of commands, including play back through said rebroadcast signal transport path of one or more auxiliary information files stored in said storage unit,  
30 interleaved with portions of said general application information signal being rebroadcast by said respective transceiver.

18. The store and forward receiver according to claim 17, wherein said command signal processor is operative to access a sequence of commands stored in said storage unit, in response to receipt of a command signal  
5 from a source other than said master site transmitter.

19. The store and forward receiver according to claim 17, wherein a respective sequence of commands stored in said storage unit includes commands that are effective  
5 to cause said respective rebroadcasting station to perform a sequence of operations at different instances in time.

20. The store and forward receiver according to claim 17, wherein a respective sequence of commands stored in said storage unit includes commands that are effective to cause said respective rebroadcasting station to perform  
5 a locally unique sequence of operations meeting network timing requirements at the same instance in time for receivers in that network grouping.

21. The store and forward receiver according to claim 17, wherein said general application information signal comprises a commercial programming digital audio  
5 stream, and wherein said respective actions associated

